

WATERPRUF SEALER



COLOURLESS SILICONE WATERPROOFER

PRODUCT DESCRIPTION

Obaproof WaterPruf Sealer is specially formulated silicone based on silane/ siloxane for impregnating to cement and other porous surfaces. It provides a good penetration capacity and good alkaline resistance.

SUITABLE FOR

1. All untreated concrete, brick and natural stonework on driveways, patios, walkways and garage floors.
2. Waterproof the back of Marble or granite
Obaproof WaterPruf Sealer can be applied to the back and sides of the marble or granite. Let the material to cure for 6 hours before installation. This will ensure that no water passes through areas that have been treated thus eliminating watermarks on surface of the marble or granite installation.
3. Against fungus growth on concrete surface
It can be apply as a primer which penetrate into the surface and thus prevent fungus growth.

TECHNICAL & PHYSICAL DATA

Colour	: Clear
Form	: Liquid
Odour	: Solvent odour
Adhesion	: Excellent adhesion to clean, damp and sound surfaces.
Coverage	: Approx. 1.5 - 3.0sq.m per litre.
Safety	: Non-hazardous.
Cleaning	: Clean tools and equipment with white spirit after use.

SURFACE PREPARATION

Ensure surfaces are clean, dry and free from dirt, grease, efflorescence (a whitish substance) that can prevent absorption of the sealer. Check all caulking and sealing is fully cured before applying Obaproof WaterPruf Sealer. The surface to be applied should be dry or damp and not wet. For new concrete surface, a minimum of 28 days is required for curing.

Application

Obaproof WaterPruf Sealer is ready to use and dilution is not required. Use a brush, roller or low-pressure air spray to apply. Application of this material will be on flooding action. Apply several coats in wet on wet basis, until the substrate is saturated. At least 2 or 3 coats are sufficient for all substrates. Do not leave long break between coats.

Apply the next when the substrates have absorbed the previous one and are no longer shiny. Any material that is not absorbed in a few minutes should be wiped up.

Note: Obaproof WaterPruf Sealer can be applied to dry and damp surfaces but not wet. Allow the surface to air dry after rain. Do not apply Obaproof WaterPruf Sealer if rain anticipated within 3 hours.

