

FLEXXI 2 IN 1



COMPOUND FLEXXI 2 IN 1

PRODUCT DESCRIPTION:

Obaproof Flexxi 2 in 1 is a plaster-based compound used for flushing joints of plaster boards. It can also be used as a putty to touch-up the fibrous plaster board and can produce a smooth fine finish using a steel trowel.

SURFACE PREPARATION

Inspect all nails and drive protruding nails below surface leaving 1/32 inch depression in surface. Make sure surfaces are clean, dry and free from foreign materials.

- Apply the mixture, filling up the joints using a steel trowel.
- Apply evenly over the joints and remove excess compound.
- Apply to fill up uneven surfaces.
- All tools to be washed with clean water and wipe dry before storing.

STORAGE

- Store at place temperature in a cool and dry location.
- Keep away from direct exposure to sunlight.

MIXING

- Fill container with clean water.
- Sprinkle the stopping compound into the water (Approx. 2 or 2.5 parts of compound to 1 part of water depending on the consistency required).
- Allow to soak for 1 to 3 minutes before mixing.
- Mix to a smooth creamy workable consistency.
- Do not over mix otherwise it will accelerate the setting time of the mixture.

TECHNICAL & PHYSICAL DATA

Colour:	White
Form:	Powder
Drying time:	Approximately 20 minutes depending on the thickness.
Cleaning:	Clean tools with water.

